



Precision balance Talent TE3102S



Standard features.

- High-grade stainless steel weighing pan
- Large, high-contrast LCD
- High level of operating convenience thanks to keys with positive click action and 2 tare keys
- Built-in application programs: counting, weighing in %, net-total formulation; averaging; toggling between 2 units
- Four digital filter levels for adaptation of the balance to the conditions at the place of use
- Bidirectional RS-232C data interface port
- ISO/GLP-compliant logging capability for calibration, adjustment and weighing data in conjunction with the optional YDP03-OCE data printer
- Mechanical protection of the weighing system against side impact and overloading
- Rugged construction; compact size; reliable weighing technology

| | |
|----------------------|-------------------|
| Readability | 0.01 g |
| Weighing capacity | 3,100 g |
| Pan size | 174x143 mm |
| Response time (avg.) | 2.5 s |
| Housing (WxDxH) | 200x270x70 mm |
| Reproducibility | $\leq \pm 0.01$ g |
| Linearity | $\leq \pm 0.02$ g |



Data printer



SartoConnect

| Key accessories | Order no. |
|--|------------|
| Data printer with date, time and statistics functions | YDP03-OCE |
| Data transfer software SartoConnect with RS-232C standard cable (1.5 m); | YSC01L |
| Test and calibration weight: 2,000 g, accuracy class E2 | YCW6228-00 |
| External rechargeable battery pack | YRB08Z |
| Carrying case | YDB01TE |
| Dust cover | 6960TE03 |