

StarterWater Analysis Portable Meter



Versatile and Portable Water Analysis Products for Wherever Your Work Takes You

After more than a century of perfecting the art of measurement through our durable weighing products, OHAUS precision is now available in a line of portable water analysis products that includes pH, conductivity, and dissolved oxygen meters that can also test for ORP and TDS. These portable meters offer convenience, reliability and durability in one compact design.

Standard Features Include:

- Intuitive Software Powers the Starter Series—Intuitive software and a well-organized display work in tandem to make operating the Starter Series a simple and straightforward task.
- Compact And Ergonomic Design Creates A User Friendly Experience—Starter portable products fit comfortably in the palm of your hand. Each also comes equipped with a retractable built-in stand that can be used to prop up the meter on a flat surface.
- Reliable Calibration Results for Accurate Measurement

 Starter tracks the accuracy of
 the calibration process right on the display so you can measure with peace-of-mind knowing
 your results will be highly precise.



99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

Starter Water Analysis Portable Meters

Portable Meters Packed with Productive Features

The Starter Series of portable water analysis meters was created with versatility in mind. They can be operated in the lab with the support of the built-in stands or in the field thanks to their lightweight design. With a clear, well-organized LCD screen and five clearly marked keys, utilizing the Starter Series is simple for novices and professionals alike. The portable Starter Series also boasts IP54 protection which shields the meter from damage by water and dust particles and it also offers an integrated labeling area which can be customized for quick identification. Each meter can store 30 sets of data memory and has the ability to quickly recall calibration data and stored information with one quick touch.

Starter 300 pH Meter

Starter 300 combines portability with precise pH measurement. An ORP or temperature electrode can also be easily connected to provide additional functionality.

- Auto buffer recognition stores calibration data and helps to avoid errors during the calibration process
- Automatic and manual temperature compensation helps ensure accurate readings

Starter 300C Conductivity Meter

Starter 300C is the reliable and accurate choice for measurement of the conductivity and TDS levels of liquids. With a variety of features that protect the meter from more extreme elements, Starter 300C can be used for a wide variety of applications.

- The 4-pole linear electrode offers a large conductivity range that safeguards itself from polarization and pollution effects
- Automatic temperature compensation with an adjustable temperature coefficient

Starter 300D Dissolved Oxygen Meter

Starter 300D provides accurate and reliable dissolved oxygen measurement that is critical to aquatic life and water quality.

- Each time the meter is calibrated, icons appear on the display to confirm the accuracy of the calibration process so you can ensure accurate measurement
- Push-button toggling between ppm, mg/L and percentage
- The galvanic electrode can be used immediately after being powered on without the wait time typically associated with dissolved oxygen meters



Specifications

Model	ST300*	ST300C*	ST300D*	
Measurement Range	0.00 – 14.00 pH –1999 – 1999 mV 0 °C – 100 °C	0.0 μS/cm − 199.9 mS/cm 0.1 mg/l − 199.9 g/l (TDS) 0 °C − 100 °C	0.0 – 199.9%; 200 – 400% 0.00 – 19.99; 20.0 – 45.0 mg/L 0.00 – 19.99; 20.0 – 45.0 ppm 0 – 50 °C	
Measurement Resolution	0.01 pH 1 mV 0.1°C	Automatic Range 0.1°C	0.1%; 1% 0.1 mg/L; 1mg/L 0.01 ppm; 0.1 ppm 0.1 °C	
Barometric Range	N/A	N/A	375 – 825 mmHg 500 – 1100 mbar 500 – 1100 hPa	
Barometric Resolution	N/A	N/A	1 mmHg 1 mbar 1 hPa	
Error Limits	± 0.01 pH ± 1 mV ± 0.5 °C	± 0.5 % of the Measured Value ± 0.3°C	± 1% ; ± 0.3 °C	
Calibration	3 Points 1 Predefined Buffer Group	1 Point 3 Predefined Standards	1 or 2 Points 100% and 0%	
Memory	30 Measurements Last Calibration Data	30 Measurements Last Calibration Data	30 Measurements Last Calibration Data	
Power Supply	4 AAA > 500 Operating Hours	4 AAA > 250 Operating Hours	4 AAA > 250 Operating Hours	
Size/Weight	90 W × 150 D x 35 H mm / 0.18 kg (Without Batteries)	90 W × 150 D x 35 H mm / 0.16 kg (Without Batteries)	90 W × 150 D x 35 H mm / 0.18 kg (Without Batteries)	
Display	Liquid Crystal	Liquid Crystal	Liquid Crystal	
Input	BNC, Impedance > $10e+12 \Omega$ Cinch, NTC $30 k\Omega$	Mini-Din	BNC, Cinch, NTC 30 kΩ	
Temperature Compensation	ATC & MTC	ATC,Linear: 0.00 %/°C – 10.00 %/°C Reference Temperature: 20 & 25 °C	ATC & MTC	
Salinity Compensation	NA	NA	0.0 to 50.0 ppt	
IP Protection	IP54	IP54	IP54	
Housing	ABS	ABS	ABS	

^{*}Portable Meters are available in different packages:

ST300

Model	Description
ST300-B	300 Meter with IP54 Sets, Electrode Clip, Wrist Strap and 4 AAA Batteries (Electrode not included)
ST300	300 Meter, ST320 3-in-1 Plastic Gel pH Electrode, and pH Buffer Powder Sachet
ST300-G	ST300-B, ST320 3-in-1 Plastic Gel pH Electrode, pH Buffer Powder Sachet (4.01, 7.00, 10.01), Portable Bag

ST300C

Model	Description
ST300C-B	Starter 300C Meter, Conductivity Standards 1413µS/cm and 12.88mS/cm (20ml bottles), IP54 Sets, Electrode Clip, Wrist Strap, 4 AAA Batteries (Electrode not included)
ST300C	300C Meter, with STCON3 4-Pole Conductivity Electrode (70 µS/cm-200ms/cm), 2 Small Bottles of Standard Conductivity Solution - 1413 µS/cm and 12.88ms/cm, IP54 Sets, Electrode Clip, Wrist Strap, 4 AAA Batteries
ST300C-G	ST300C-B, STCON3 4-Pole Conductivity Electrode (70 µS/cm - 200 mS/cm), Portable Bag

ST300D

2.3002		
Model	Description	
ST300D-B	300D Meter with IP54 Sets, Electrode Clip, Wrist Strap and 4 AAA Batteries (Electrode not included)	
ST300D	300D Meter with STDO11 Galvanic DO Electrode, and STTEMP30 Temperature Electrode	
ST300D-G	ST300D-B with STDO11 Galvanic DO Electrode, STTEMP30 Temperature Electrode, Portable Bag	



Starter Water Analysis Portable Meters

300 Compatible Electrodes

-	
Description	Model
3-in-1 Plastic Refillable pH Electrode	ST310
2-in-1 Plastic Refillable pH Electrode	ST210
3-in-1 Plastic Gel pH Electrode	ST320
2-in 1 Glass Muddy Sample pH Electrode	ST230
2-in-1 Glass Pure Water Sample pH Electrode	STPURE
Temperature Electrode	STTEMP30
Gel Plastic ORP Electrode	STORP1
Refillable Glass ORP Electrode	STORP2
2-in-1 Glass Micro Sample pH Electrode, 80 x 5mm	STMICRO5
2-in-1 Glass Micro Sample pH Electrode, 150 x 8mm	STMICRO8
3-in-1 Glass pH Electrode	ST350
2-in-1 Glass Double-salt-bridge pH Electrode Can Test Tris-buffer	ST260
2-in-1 Plastic Flat pH Electrode	STSURF

300C Compatible Electrodes

Description	Model
4-Pole Conductivity Electrode (70 μS/cm-200mS/cm)	STCON3*
2-Pole Pure Water Conductivity Electrode (0.02 – 200 μS/cm)	STCON7

*In this range 70 μ S/cm-200mS/cm the measurement accuracy is 0.5%. STCON3 can also measure conductivity value which is below 70 μ S/cm, the measurement will be less accurate (approximately 1% to 5%).

300D Compatible Electrodes

Description	Model	
Temperature Electrode	STTEMP30	
Galvanic DO Electrode	STDO11	

Compliance

• Electromagnetic Compatibility: FCC Part 15 Class B; ICES-003 Class B

Buffers and Accessories

Description	I N	200	2006	2000
Description	Item Number	300	300C	300D
pH Buffer Powder Sachet (4.01; 7.00; 10.01)	83033971	•		
pH1.68 250ml Solution	30100424	•		
pH4.01 250ml Solution	30100425	•		
pH6.86 250ml Solution	30100426	•		
pH7.00 250ml Solution	30100427	•		
pH9.18 250ml Solution	30100428	•		
pH10.01 250ml Solution	30100429	•		
pH12.45 250ml Solution	30100440	•		
pH Electrode Reference Electrolyte	30059255	•		
pH Electrode Protection Solution (3M KCI)	30059256	•		
pH Sensor Protection Bottle (10 in bag)	30064800	•		
Cond 10 µS/cm 250ml	30100441		•	
Cond 84 µS/cm 250ml	30100442		•	
Cond 1413 μS/cm 250ml	30100443		•	
Cond 12.88 mS/cm 250ml	30100444		•	
Dissolved Oxygen Zero Oxygen Chemicals	30059257			•
IP54 Seal Kit	83032962	•	•	•
Wrist Strap	83032963	•	•	•
Electrode Clip	83032964	•	•	•
Portable Bag	30031635	•	•	•



99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431



