

# HOT PLATE FAITHFUL



Model		SH-5	SH-8	SH-9
		SH-5B	SH-8B	SH-9B
		SH-II-5B	SH-II-8B	SH-II-9B
Function	Max Temp. (°C)	SH-5,SH-8,SH-9: 320°C SH-5B,SH-8B,SH-9B: 350°C SH-II-5B,SH-II-8B,SH-II-9B: 400°C		
Structure	Outer Shell	Iron plate welding, surface spraying		
	Hot plate	Aluminum tensile: SH-5, SH-5B,SH-8,SH-8B, SH-9, SH-9B: Graphite Plate: SH-II-5B, SH-II-8B,SH-II-9B:		
	Heating power(W)	SH-5: 800 SH-5B: 1200 SH-II-5B: 1800	SH-8: 1500 SH-8B: 2400 SH-II-8B: 3000	SH-9: 2200 SH-9B: 3500 SH-II-9B: 4500
Controller	Setting method	Scale: SH-5, SH-8, SH-9 Digital: SH-5B,SH-8B,SH-9B, SH-II-5B, SH-II-8B, SH-II-9B		
	Timer	No / Digital		
	Temperature sensor	K model		
	Temp. accuracy	SH-5,SH-8,SH-9: ±10% SH-5B,SH-8B,SH-9B,SH-II-5B,SH-II-8B,SH-II-9B: ±1%		
	Plate Temp. Uniformity	SH-5,SH-8,SH-9: ±15% SH-5B,SH-8B,SH-9B,SH-II-5B,SH-II-8B,SH-II-9B: ±10%		
Specification	Exterior size (W*L*H) (mm)	340*370*220	420*500*220	470*650*220
	Packing size (W*L*H) (mm)	SH-5 / SH-5B: 520*380*250 SH-II-5B: 550*410*270	SH-8 / SH-8B: 560*520*250 SH-II-8B: 600*560*270	SH-9 / SH-9B: 660*620*250 SH-II-9B: 700*660*270
	Plate size (mm)	300*300	350*450	400*600
	Plate load	20KG	30KG	40KG
	Power supply (50/60Hz)	220V		
	NW/GW (kg)	SH-5 / SH-5B: 9 /10 SH-II-5B: 12 /13.5	SH-8 /SH-8B: 11 /12 SH-II-8B: 19 /20	SH-9 / SH-9B: 15 /17 SH-II-9B: 28 / 30

Note: SH-9B, SH-II-9B: without plug.