

SAUL MINEROFF ELECTRONICS, Inc.

Manufacturer & Distributor of Information Gathering Devices
574 Meacham Avenue, Elmont, New York 11003 USA
Phone 516.775.1370 Fax 516.775.1371 Email TapeNixon@aol.com

OLYMPUS

Olympus Binoculars



WideView 8-15x25

[Click Here to Order](#)

The WideView 8-15x25 allows you to change your viewing angle between 56° and a wide 70° so you'll see more and be able to track fast moving objects with ease. Couple that with the binoculars' impressive zoom capability, and you'll encounter some of the sharpest and most-detailed close-up images possible in a zoom model. The stylish WideView 8-15x25 binoculars also boast multi-coated, aspherical lenses

Features & Benefits

- ONLY wide-angle Compact Zoom binocular
- Extra wide angle of view ($56^\circ - 70^\circ$) to see more and watch fast moving objects more easily (an increase of approx. 40% over conventional models with a $35^\circ - 50^\circ$ viewing angle)
- Multi-coated and aspherical lenses to considerably reduce distortion
- High index BaK-4 porro prisms to provide great clarity and brightness, for both day and evening occasions/events
- UV protection
- Stylish, ergonomic design with metallic-silver finish and non-slip rubber handgrips so you can hold them comfortably for extended periods of time
- Built-in dioptic correction adjusts to individual requirements
- Ideal for outdoor use: spectator sports, nature watching, hiking and entertainment events

Technical Specifications

Type	Porro Prism
Magnification	8 - 15x
Objective Lens Diameter	25 mm
Exit Pupil Diameter	3.1 - 1.7 mm
Rear Angle of View	$7.0 \sim 4.7^\circ$
Apparent Angle of View	$56 \sim 70.5^\circ$
Field Of View at 1000 yds	366 - 246 ft. / 122 - 82 m
Relative Brightness	9.8 - 2.8
Eye Relief	8.9 - 9.2 mm
Diopter Adjustment Range	Over $\pm 2m^{-1}$
Eye Interval Adjustment Range	$60 \sim 70$ mm
Near Focus Distance	16.4 ft. / 5 m
Weight	16.4 oz. / 465 g
Dimensions	4.9 in. (W) x 5.0 in. (H) x 2.4 in. (D) / 124.5 mm (W) x 126.5 mm (H) x 61 mm (D)
Lens Composition	7 elements in 5 groups
Coating	n/a
Features	n/a